

MV 260-17,5m

Solo con braccio da 16 m
Only with 16 m jib

Dimensions and configurations shown:

- Top configuration: 30° angle, 13.920 m horizontal reach, 22.300 m vertical height, kg 500 load.
- Middle configuration: 20° angle, 16.300 m horizontal reach, 20.400 m vertical height, kg 450 load.
- Bottom configuration: 10° angle, 17.000 m horizontal reach, 17.700 m vertical height, kg 450 load.
- Main configuration: 17.600 m total height, 14.250 m jib height, 10390 m horizontal reach, kg 1600 and kg 1300 loads.
- Additional configuration: 13.260 m horizontal reach, kg 750 load.
- Base configuration: 8.900 m horizontal reach, kg 1300 load.

Table of capacities (kg) vs. height (m):

m	6.1	7	8	9	10	11	12	13	14	15	16	17.5
kg	1600	1359	1156	1003	885	788	710	645	590	543	502	450



STANDARD FEATURES



EQUIPEMENT DE SERIE



SERIENAUSSTATTUNG



COTACION DE SERIE

Levantamiento a cuatro velocidades, carro y rotación a tres velocidades con control electrónico, galvanización de la estructura, contrapeso, brazo empinable, carro rampante con motor y fin de carrera en la base de la torre, funcionamiento con brazo plegado, faccionamiento por pulsadores via cable, cárter de protector para corona de giro y mecanismos, predisposición para autocontrapeso y radiocontrol, armario eléctrico de acero inox, documentación según normas CEE.

P1	990 kg	2490 kg	4045 kg	3445 kg
P2	3485 kg	3785 kg	4130 kg	4030 kg